



Product Comparison

Are you comparing
Apples



to Apples?

Cres Cor RO-151-FUA-18DE	FWE RH18HO	Cres Cor Advantage
CAPACITY: (18) 18" x 26" or (36) 12" x 20" pans, 18 sets of stainless steel wire universal angles on 1-1/2" centers.	CAPACITY: (18) 18" x 26" pans, 18 welded rod-style tray slides, nickel chrome plated on 1-1/2" spacing.	Cres Cor's heavy duty solid stainless steel angles won't rust or break.
BODY CONSTRUCTION: 22 ga. stainless steel body with 18 ga. stainless steel internal frame. Automatic water fill hook-up at rear. Interior coved corners. 1-1/2" fiberglass in doors top and base, 2" in sidewalls.	BODY CONSTRUCTION: 18 ga. stainless steel throughout. Welded tubular base. Connect to water supply through saddle valve and tubing kit at rear (supplied). Interior coved corners. Fiberglass minimum 2" max 4" throughout.	Cres Cor has a strong internal frame for structure and securing hardware. Thick insulation throughout has better heat retention. Coved corners are easier to clean and sanitize.
DOOR: 22 ga. stainless steel dutch doors. Field reversible. Embossed pan stop. Anti-microbial ceramic magnetic pull latch. Self-closing, lift-off hinges of heavy duty steel. Silicone door gaskets	DOOR: 18 ga. stainless steel dutch doors. Not field reversible. Magnetic door latch. Lift-off hinges. Gasketless doors.	Anti-microbial latches protect against spreading germs. Silicone door gaskets prevent temperature loss with proper seal.
CASTERS: 5" dia. swivel modulus, two with brakes.	CASTERS: 5" dia., polyurethane, two with brakes.	High modulus wheel for quiet rolling and shock absorption on uneven or rough surfaces.
CONTROLS: Digital LED solid state controls top mounted. No Probe	CONTROLS: LED thermometer, analog controls. (12) programmable menu buttons. On/off switch. Food probe ready, probe not included.	Easy to read LED display with more reliable push button power button.
ELECTRICAL: 12,000 Watts, 208 Volt, 3 Phase, 50 Amp. 12,000 Watts, 240 Volt, 3 Phase, 50 Amp. 10' 12/3 ga. NEMA 15-50 cord and plug NSF, CSA-US, CSA-C listed	ELECTRICAL: 11,170 Watts, 208 Volt, 3 Phase, 50 Amp. 14,720 Watts, 240 Volt, 3 Phase, 50 Amp. NEMA 15-50 cord and plug unknown length. NSF, CSA-US, CSA-C listed	Quick to reheat after door opening, and longer cord gives more room for access while cabinet is plugged in.
EXTERIOR DIMENSIONS: 37-3/4"W x 28-3/4"D x 73-11/16"H	EXTERIOR DIMENSIONS: 34-1/2"W x 27-3/5"D x 76-1/10"H	
SHIP WEIGHT: 392 lbs.	SHIP WEIGHT: 600 lbs.	
WARRANTY: 3-Year Parts, 1-Year Labor 5-Year parts for K-12 schools	WARRANTY: 2-Year Parts, 1-Year Labor	Warranty is longer on parts coverage and better for K-12 schools!
December, 2017 List Price: \$18,662	December, 2013 List Price: \$16,886	